

**Schill + Seilacher**

Technical Data Sheet

STRUKTOL® LD 183

Antifoaming Agent and Dewebbing Agent for NR Latex

Composition

Mixture of polyethers, hydrocarbons and inorganic fillers

Properties

Appearance		light-coloured liquid
Density at 20 °C	[kg/m ³]	960
pH-value		9
Physiological behaviour		refer to safety data sheet
Storage stability		at least 6 months under normal storage conditions
Packing		100 kg drums 5 kg + 25 kg cans

The data given are typical values which are not intended for use in preparing specifications. For test methods refer to the corresponding supplement.



Schill + Seilacher "Struktol" GmbH
Moorfleeter Str. 28
D-22113 Hamburg

Fon: +49 40 733 62-0
 Fax: +49 40 733 62-194
 E-Mail: info@struktol.de
 Internet: www.struktol.de

Recommendations for Application

STRUKTOL LD 183 is an antifoaming agent and dewebbing agent for NR latex.

STRUKTOL LD 183 complies with Recommendation XXI of BfR.

STRUKTOL LD 183 is preferably used as a masterbatch having the following composition:

STRUKTOL LD 183	1 part
Deionized water	1 part

Dosage

0.05 - 0.1 %

As masterbatch: 0.1 - 0.2 %

The suggestions for application and usage of our products as well as possible proposed formulations are meant to advise only to the best of our knowledge. This information is without obligation and does not release customers from their own testings to ensure suitability for intended processes and use. Liability is only accepted in case of intention or gross negligence. Liability for any defects caused by minor negligence are not accepted. Each producer is responsible and liable to observe legislation and patent rights of third parties.

This new leaflet replaces all previously printed documentation.
Alterations reserved. 11/2004

Schill + Seilacher "Struktol" GmbH Moorfleeter Straße 28 22113 Hamburg Germany
Phone: +49 40 73362-0 Fax: +49 40 73362-194 E-Mail: info@struktol.de