

Technical Data Sheet

STRUKSILON® E 35

Composition

Aqueous emulsion of medium-viscosity polydimethylsiloxane with non-ionic surfactants

Properties

Appearance		milky-white liquid
Density	[kg/m ³]	980
pH value		6
Active content	[%]	35
Viscosity of silicone fluid at 25 °C	[mm ² /s]	350
Physiological behaviour		refer to safety data sheet
Packing		25 kg can, 200 kg drum, 1000 kg IBC
Storage stability		at least 12 months in original-sealed containers at transport and storage temperatures till 40 °C Attention: Protect from frost!



Application Recommendation

STRUKSILON® E 35 is a solvent-free, aqueous silicone emulsion developed for the rubber, plastic, foundry and ceramic industry. In these fields the emulsion is usually applied as mould release agent. Additionally this product is partly applied to finishing textiles and to improve their handle and slip. During production of yarn the emulsion reduces friction and thus avoids undesirable crack of the yarn. In the formulation of polishing agents the gloss is increased and formation of lube is reduced. Additionally the emulsion can be applied when producing ironing sprays, cockpit sprays and for re-wetting of offset printing. And STRUKSILON® E 35 is used for demoulding and hydrophobing of technical glassware.

Due to the low viscosity STRUKSILON® E 35 is easy to handle and to dose. It consists exceptionally biodegradable surfactants. The small particle size enables a fine dispersion of the emulsion on the surface and the formation of a coherent film.

The release, slip and hydrophobic properties of STRUKSILON® E 35 are excellent.

To achieve the required release and lubricant effect only little amounts of STRUKSILON® E 35 need to be applied. The emulsion can be diluted to an active content of 0.5 %. Depend on the concentration of the diluted dispersion, the storage stability is limited and the final product should be used in shorter times.

It is the perfect product for formulators or re-filling companies. It can be easily repacked and sold at lower concentrations. The recommended dilution concentration here is maximum 1 part STRUKSILON® E 35 with 3 parts water.

STRUKSILON® E 35 can be applied onto the surface by spraying, dipping, rolling and brushing.

In case of prolonged storage silicone emulsions may show differences in concentration due to condensation of water at the top of the container and/or slightly creaming.

Attention: Stir properly before use.

Disclaimer:

This publication is not a specification and does not contain any instruction manual or operating guidelines. It is provided for information purposes only and without any responsibility. Schill + Seilacher "Struktol" makes no representations about the accuracy, reliability or completeness of the information in this publication. We reserve the right to revise our not specified products and the information at any time without notice. The information in this publication is based on the present state of our knowledge and experience and serves the general description of our products and their possible applications. Our technical advice and recommendations, whether verbal, in writing or by way of trials, do not absolve the recipient, on account of the many outside influences which may affect the product use and application, from their own testing and trials. A legally binding assurance based on the information contained herein regarding particular properties or the suitability for definite customer applications cannot be derived from our information.

In accordance with the provisions of our General Terms and Conditions of Sale and Delivery, which can be accessed under www.struktol.de, Schill+Seilacher "Struktol" excludes liability for slightly negligent breaches of obligations arising from the use of the information contained in this publication, provided that they do not relate to damage from injury to life, limb or health or guarantees or claims under the Product Liability Act are affected. Furthermore, the liability for the breach of obligations, the fulfilment of which is essential for the proper execution of the contract and on the observance of which the customer may regularly rely, remains unaffected. The same applies to breaches of duty by our agents.

This technical datasheet is created automatically and is valid without signature.

